

Portable PA Systems Systems

TXA-624CD/SW

Order No. 0179150



Portable amplifier system, with integrated 2-channel multifrequency receiver unit in UHF PLL technology and CD player with anti-shock system.

- Operation via mains connection or built-in rechargeable lead gel battery 12 V/7.2 Ah (operating time: up to 10 hours), integrated automatic battery charging
- For mobile applications, e.g. sales events, lectures
- 2 x 16 selectable UHF frequencies (863.1-864.9 MHz)
- High-quality CD player with slot-in mechanism, USB port for external storage media, reproduction of audio CD, CD-R, MP3 CD
- 2-way bass-reflex speaker system
- Excellent sound characteristics due to 20 cm (8", Fatial) bass speaker and 25 mm (1") tweeter
- 1 input via comb. jack mic (XLR)/line (6.3 mm), gain control, 3-way equalizer
- Supplied with practical protective bag which can stay on during operation

Model	TXA-624CD/SW
Rated power (P _{RMS})	50 W
Peak output power	75 W
Frequency range	50-18,500 Hz
Carrier frequency	863.1-864.9 MHz
Operating range	≈ 30 m
Inputs	4.5 mV, XLR (mic), 30 mV, 6.3 mm jack (line), 200 mV, RCA (line)
Equalizer, bass	±12 dB/55 Hz
Equalizer, midrange	±6 dB/1 kHz
Equalizer, treble	±8 dB/10 kHz
Power supply	~ 230 V/50 Hz/60 VA, rech. batt. 12 V/7.2 Ah
Dimensions	235 x 450 x 280 mm
Weight	9.7 kg
Connections	1 x XLR (mic), 1 x 6.3 mm jack (line), 1 x RCA L/R (line), 1 x RCA L/R (mix out, link), 1 x SPEAKON (ext. speakers)

Matching microphone transmitters or pocket transmitters are available at option, e.g. TXA-800HSE or TXA-800HT.

Licence-free in the EU.



TXA-604/SW

Order No. 0179140



Portable amplifier system, with integrated 2-channel multifrequency receiver unit in UHF PLL technology.

- Operation via mains connection or built-in rechargeable lead gel battery 12 V/7.2 Ah (operating time: up to 10 hours), integrated automatic battery charging
- For mobile applications, e.g. sales events, lectures
- 2 x 16 selectable UHF frequencies (863.1-864.9 MHz)
- Class D power amplifier
- Cabinet with durable two-component PU coating
- 2-way bass-reflex speaker system
- Excellent sound characteristics due to a 20 cm (8", FAITAL) bass speaker and 25 mm (1") horn tweeter
- 1 input via comb. jacks mic (XLR)/line (6.3 mm), gain control, 3-way tone control
- 1 stereo line input via RCA jacks, gain control, common 2-way tone control
- Adjustable talkover
- Link connections (RCA) for combining several amplifier systems TXA-624CD/SW or TXA-604/SW

Model	TXA-604/SW
Rated power (P _{RMS})	50 W
Peak output power	75 W
Frequency range	50-18,500 Hz
Carrier frequency	863.1-864.9 MHz
Operating range	≈ 30 m
Inputs	4.5 mV, XLR (mic), 30 mV, 6.3 mm jack (line), 200 mV, RCA (line)
Equalizer, bass	±12 dB/55 Hz
Equalizer, treble	±8 dB/10 kHz
Power supply	~ 230 V/50 Hz/60 VA, rech. batt. 12 V/7.2 Ah
Dimensions	235 x 450 x 280 mm
Weight	9.7 kg
Connections	1 x XLR (mic), 1 x 6.3 mm jack (line), 1 x RCA L/R (line), 1 x RCA L/R (mix out, link), 1 x SPEAKON (ext. speaker)

- SPEAKON connection (4 Ω) for external speaker TXB-602/SW
- Supplied with practical protective shoulder bag which can stay on during operation



Matching microphone transmitters or pocket transmitters are available at option, e.g. TXA-800HSE or TXA-800HT.

Licence-free in the EU.

TXB-602/SW

Order No. 0130050

Speaker system, 50 W, 4 Ω, suitable for portable amplifier systems TXA-604/SW and TXA-624CD/SW.

- Cabinet with durable two-component PU coating
- 2-way bass-reflex speaker system
- Excellent sound characteristics due to a 20 cm (8", FAITAL) bass speaker and 25 mm (1") horn tweeter
- Frequency range: 60-18,500 Hz

- SPEAKON connection
- Stand sleeve
- Supplied with practical protective shoulder bag which can stay on during operation
- Dimensions: 240 x 400 x 290 mm
- Weight: 8.2 kg

