



## IT-400DT

Order No.: 0163870

**Price upon request**

### PRODUCTINFOS

#### Weatherproof active horn speaker (music horn), 2-way technology

- With integrated Dante<sup>®</sup> module and DSP
- DSP-controlled 20 W amplifier
- Power supply via PoE (Power over Ethernet)
- Weatherproof and IP66 certified
- Very wideband sound with a distinct bass volume, even at very high volume levels
- 16 cm bass-midrange speaker and 25 mm (1") horn
- Robust plastic housing
- Supplied with mounting bracket and screws made of stainless steel

System requirements Dante<sup>®</sup>: Windows\* 7/8.1/10 or MacOS 10.9.5/10.10.5/10.11

#### Please note:

32-bit applications, including the current version of the DSP controller, are no longer supported under the MacOS version 10.15 (Catalina). The controller software is currently being updated for 64-bit MacOS Catalina. Users of older MacOS versions as well as Windows users are not affected by this change.

Apple's announcement will give you further information on the change to 64-bit technology.

## TECHNICAL SPECIFICATIONS

### IT-400DT

Active/passive	active
Transmission method	Dante®
Total output power	20 W
Power rating (RMS)	20 W
Frequency range	100-20,000 Hz
Input signal	Dante®
Number of speakers	2
Sensitivity	98 dB/W/m
Max. rated SPL	112 dB
Radiation angle, horizontal	100°
Radiation angle, vertical	60°
Features	2-way
Housing material	ABS
Colour	grey
Mounting device	stainless steel mounting bracket
Protection class	IP66
Admiss. ambient temp.	-20 °C to +50 °C
Power supply	PoE
Dimensions	420 x 335 x 400 mm
Width	420 mm
Height	335 mm
Depth	400 mm
Weight	6.12 kg
Inputs	1 x RJ45
Other features	weatherproof