



MOVE-12PMK2

Order No.: 1000227

PRODUCTINFOS

Professional PA speaker system, 350 W, 8 Ω

- Compact professional full range bass-reflex system
- Cabinet made of birch plywood
- 30 cm (12", FaitalPro 12PR300) bass speaker
- 25 mm (1", 44 mm voice coil, Celestion CDX1-1747) horn tweeter, can be turned by 90°
- Switchable between passive operation and bi-amp active operation
- Neutral sound tuning
- 'Catch & Carry' carrying handle
- M8 threaded inserts for suspended installation
- 2 x NEUTRIK SPEAKON terminal, in/out
- Stand sleeve, robust front grille

TECHNICAL SPECIFICATIONS

MOVE-12PMK2

Active/passive passive

Transmission method cable

MOVE-12PMK2

Total power rating	700 W
Power rating (RMS)	350 W
Impedance	8 Ω
Frequency range	45-20,000 Hz
System	2-way bass-reflex
Bass speaker	30 cm (12", FaitalPro 12PR300)
Tweeter	dyn. 25 mm mid-high range speaker (1", 44 mm voice coil, Celestion CDX1-1747)
Number of speakers	2
Speaker size	30 cm (12")
Sensitivity	98 dB/W/m
Max. rated SPL	124 dB
Beam angle	H: 80°/V: 40°, horn can be turned by 90°
Radiation angle, horizontal	80°
Radiation angle, vertical	40°
Housing material	birch plywood
Colour	black
Mounting device	M8 threaded inserts
Admiss. ambient temp.	0-40 °C
Dimensions	350 x 620 x 385 mm
Width	350 mm
Height	620 mm
Depth	385 mm
Weight	16.4 kg
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON par.out
Accessories	MOVE-12/BAG
Packing dimensions (W x H x L)	0.4 x 0.65 x 0.37 m
Gross weight	18.4 kg
Net weight	16.39 kg