



ECM-925P

Order No.: 23.1990

EUR 104,90

RRP *

PRODUCTINFOS

Electret phantom directional microphone,

with switchable pick-up pattern, from normal to supercardioid with high sensitivity.

- Particularly suitable for outdoor recordings, e.g. film productions
- Microphone windshield

TECHNICAL SPECIFICATIONS

ECM-925P

Type	directional microphone
Transmission method	cable
Polar pattern	cardioid/supercardioid
System	electret

ECM-925P

Carrier frequency range	-
Transmitting power	-
Power supply	-
Operating time	-
Audio frequency range	80-12000Hz
Nominal impedance	normal 1 k Ω , tele 2.3 k Ω
Sensitivity	3/15 mV/Pa
S/N ratio	>40dB
Maximum sound pressure	120dB
Power supply	DC 9-48 V, phantom power1.5 V battery
Gooseneck length	-
Material (housing/cabinet)	metal
Admiss. ambient temp.	0-40°C
Dimensions	Ø 25 mm x 285 mm
Weight	460g
Cable	5m
Connection	XLR

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.