



EDL-412/WS

Order No.: 16.1860

EUR 89,90

RRP *

PRODUCTINFOS

Weatherproof PA ball speaker

- 100 V line technique or 8 Ω operation
- White ABS housing (self-extinguishing, complies with standard UL 94V-0)
- Supplied with 480 cm connection cable and canopy

TECHNICAL SPECIFICATIONS

EDL-412/WS

Active/passive	passive
Operating voltage	100 V
Impedance	8 Ω
Frequency range	160-20000 Hz
Amplifier power	-

EDL-412/WS

Max. power	-
THD	-
S/N ratio	-
Input signal	-
System	-
Bass speaker	-
Midrange speaker	-
Tweeter	-
Number of speakers	1
Speaker size	-
Power rating	10/5/2.5 W
Peak music power output	-
Sensitivity	92 dB/W/m
Max. rated SPL	-
Radiation angle, horizontal	-
Radiation angle, vertical	-
Material (housing/cabinet)	ABS, UL 94V-0
Colour	white
Mounting facility	cable with canopy
Protected against ball rebound	-
Protective class	IP44
Admiss. ambient temp.	-
Power supply	-
Dimensions	Ø 184 mm
Width	Ø184 mm
Height	-
Depth	-
Weight	1,7 kg
Inputs	-
Outputs	-
Other features	-

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.