



TXS-840

Order No.: 24.0850

EUR 124,90

RRP *

PRODUCTINFOS

Receiver unit,

matching transmitters with the same carrier frequency.

- Switching diversity system with folding antennas
- Squelch control
- Volume control
- XLR output and 6.3 mm output
- LEDs for indicating power, AF peak and transmitter status
- Supplied with PSU

Licence-free in the EU.

TECHNICAL SPECIFICATIONS

TXS-840

General information	-
Type	receiver
Carrier frequency range	863,05MHz
Audio frequency range	50-15000Hz
Channels	1
THD	<0,6%
Dynamic range	>110dB
RF S/N ratio	-
Operating time	-
Admiss. ambient temp.	0-40°C
Power supply	-
Dimensions	-
Total weight	-
Connections	-
Specifications transmitter	-
Transmitting power	-
Operating range	-
Power supply transmitter	-
Width transmitter	-
Height transmitter	-
Depth transmitter	-
Weight transmitter	-
Connections transmitter	-
Specifications receiver	-
Audio signal receiver	0.75 V/5 kΩ (jack)60 mV/600 Ω (XLR, bal.)
Power supply receiver	via suppl.plug-in PSU
Width receiver	220mm
Height receiver	114mm
Depth receiver	40mm
Weight receiver	550g
Connections receiver	1 x XLR, bal.,1 x 6.3 mm jack, unbal.

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.